



AMAZONLVT®
luxury vinyl tiles

VOLUME 3



FULL COLOUR RANGE:



**2311
gilded
honey**



**2312
cinnamon
wood**



**2313
relic
rosette**



**2314
java
dawn**



**2315
acacia
fall**

WARM WOOD

- Dimensions** 184mm x 950 mm
- Overall Gauge** 3mm (thicker gauge available)
- Wear Layer** 0.3mm (thicker wear layer available)
- Packaging** 19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



2311
gilded honey

WARM WOOD

Dimensions 184mm x 950 mm
Overall Gauge 3mm (thicker gauge available)
Wear Layer 0.3mm (thicker wear layer available)
Packaging 19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



WARM WOOD

Dimensions	184mm x 950 mm
Overall Gauge	3mm (thicker gauge available)
Wear Layer	0.3mm (thicker wear layer available)
Packaging	19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



LVT WIDE V3 ▶ 2311 glided honey

WARM WOOD

Dimensions 184mm x 950 mm
Overall Gauge 3mm (thicker gauge available)
Wear Layer 0.3mm (thicker wear layer available)
Packaging 19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



2312
cinnamon wood

WARM WOOD

Dimensions 184mm x 950 mm
Overall Gauge 3mm (thicker gauge available)
Wear Layer 0.3mm (thicker wear layer available)
Packaging 19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



WARM WOOD

Dimensions	184mm x 950 mm
Overall Gauge	3mm (thicker gauge available)
Wear Layer	0.3mm (thicker wear layer available)
Packaging	19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



LVT WIDE V3 ▶ 2312 cinnamon wood

WARM WOOD

Dimensions 184mm x 950 mm
Overall Gauge 3mm (thicker gauge available)
Wear Layer 0.3mm (thicker wear layer available)
Packaging 19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



2313
relic rosette

WARM WOOD

- Dimensions** 184mm x 950 mm
- Overall Gauge** 3mm (thicker gauge available)
- Wear Layer** 0.3mm (thicker wear layer available)
- Packaging** 19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



WARM WOOD

Dimensions	184mm x 950 mm
Overall Gauge	3mm (thicker gauge available)
Wear Layer	0.3mm (thicker wear layer available)
Packaging	19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



LVT WIDE V3 ▶ 2313 relic rosette

WARM WOOD

Dimensions 184mm x 950 mm
Overall Gauge 3mm (thicker gauge available)
Wear Layer 0.3mm (thicker wear layer available)
Packaging 19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



2314
java dawn

WARM WOOD

- Dimensions** 184mm x 950 mm
Overall Gauge 3mm (thicker gauge available)
Wear Layer 0.3mm (thicker wear layer available)
Packaging 19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



WARM WOOD

Dimensions	184mm x 950 mm
Overall Gauge	3mm (thicker gauge available)
Wear Layer	0.3mm (thicker wear layer available)
Packaging	19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



LVT WIDE V3 ▶ 2314 java dawn

WARM WOOD

Dimensions 184mm x 950 mm
Overall Gauge 3mm (thicker gauge available)
Wear Layer 0.3mm (thicker wear layer available)
Packaging 19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



2315
acacia fall

WARM WOOD

- Dimensions** 184mm x 950 mm
- Overall Gauge** 3mm (thicker gauge available)
- Wear Layer** 0.3mm (thicker wear layer available)
- Packaging** 19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



WARM WOOD

Dimensions	184mm x 950 mm
Overall Gauge	3mm (thicker gauge available)
Wear Layer	0.3mm (thicker wear layer available)
Packaging	19pcs / 35.50sf





AMAZONLVT®
luxury vinyl tiles

VOLUME 3



WARM WOOD

Dimensions	184mm x 950 mm
Overall Gauge	3mm (thicker gauge available)
Wear Layer	0.3mm (thicker wear layer available)
Packaging	19pcs / 35.50sf



WARM WOOD

PRODUCT SPECIFICATION

Attributes

Dimensions	184mm x 950mm
Overall Gauge	3mm (thicker gauge available)
Wear layer	0.3mm (thicker wear layer available)
Packaging	19pcs / 35.50sf

TECHNICAL SPECIFICATIONS

Fire

Smoke

Heat Stability

Abrasion Resistance

Flexibility

Perpendicularity

Slip Resistance

Static Load Limit

Radiant Heat Compatibility

Castor Chair Sustainability

ASTM E84, ASTM E648, Melkel Burner
ONORM B3800

KSM 3802

ASTM D3884

EN 345 Method A

KSF 3802

ASTM 1028

ASTM F970-93

Yes

Yes

≥75, Class 1, Passed

Q1

0.3mm

0.1% Loss

Pass 20mm Mandrel

+0.2mm

ADA Wet/Dry Requirements for
Level Surfaces

1500 psi

Below 85°F/28°C

Excellent



AMAZONLVT[®]
luxury vinyl tiles

VOLUME 3